

EDGEWOOD

CHEMICAL BIOLOGICAL CENTER

U.S. ARMY SOLDIER AND BIOLOGICAL CHEMICAL COMMAND

ECBC-TR-297

QUANTITATIVE INFRARED REFERENCE LIBRARY VOLUME I

John Ditillo Christopher C. Keiser

CB SERVICES DIRECTORATE

Barry R. Williams

EAI CORPORATION Abingdon, MD 21009

July 2003



Approved for public release; distribution is unlimited.



20030929 077

Disclaimer

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorizing documents.

REPORT DOCUMENT	TATION PAGE			Approved 3 No. 0704-0188
searching existing data sources, gat comments regarding this burden est Washington Headquarters Services.	ction of information is estimated to av hering and maintaining the data need imate or any other aspect of this colle Directorate for Information Operation f Management and Budget, Paperwor	ed, and completing and ction of information, inc as and Reports, 1215 J	d reviewing the cluding sugges efferson Davis	collection of information. Send tions for reducing this burden, to Highway, Suite 1204, Arlington.
1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE 2003 July	3. REPORT TYPE AN Final; 02 Fe		
4. TITLE AND SUBTITLE	2003 July	Tillal, 02 1		DING NUMBERS
Quantitative Infrared Refe Volume I	erence Library		PR-	2VJRZZ
6. AUTHOR(S) Ditillo, John; Keiser, Chris Williams, Barry R. (EAI C	• •			
7. PERFORMING ORGANIZATION NAM	ME(S) AND ADDRESS(ES)			RMING ORGANIZATION T NUMBER
•	BB-RCB-C, APG, MD 2101 8 Continental Drive, Abingd			BC-TR-297
9. SPONSORING/MONITORING AGE	NCY NAME(S) AND ADDRESS(ES)			SORING/MONITORING CY REPORT NUMBER
11. SUPPLEMENTARY NOTES			<u> </u>	
12a. DISTRIBUTION/AVAILABILITY STA	ATEMENT		12b. DISTR	RIBUTION CODE
Approved for public release	e; distribution is unlimited.			
13. ABSTRACT (Maximum 200 words)				
Aberdeen Proving Ground, and sample analysis for a chemical disposal sites, and these tasks, the organization instrument of interest for the cell Fourier Transform Infrainfrared band. Infrared det The gas cell used has a 2. resolution. The experiment sarin (GB), distilled mustar	Il Biological Applications and MD, is actively involved in variety of missions. These and environmental assessme on is continually examining his study was the TravellR bared (FTIR) Spectrometer direction is performed with a It 4-m path length, L. Data was run with a series of quality and so	Chemical Warfa include CWM invents. To enhance and evaluating roy Sensir, Inc. It esigned to meas DTGS detector thas acquired by cuantitative conce	re Materie vestigation e CBARR's new techno is a lightwe ure and co nat operate o-adding 6	I (CWM) air monitoring s, remediation of ability to accomplish alogies in this arena. The eight, portable, closed allect radiation in the mides at room temperature.
14. SUBJECT TERMS				15. NUMBER OF PAGES
Chemical warfare materiel Chemical warfare agents Infrared spectroscopy	Vapor phase spe Infrared spectra FTIR	ectra		70
				16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	9. SECURITY CLASSIFIC OF ABSTRACT UNCLASSI		20. LIMITATION OF ABSTRACT UL

Blank

PREFACE

The work described in this report was authorized under Project No. 2VJRZZ. The work was started in February 2002 and completed in June 2002.

The use of either trade or manufacturers' names in this report does not constitute an official endorsement of any commercial products. This report may not be cited for purposes of advertisement.

This report has been approved for public release. Registered users should request additional copies from the Defense Technical Information Center, unregistered users should direct such requests to the National Technical Information Center.

Blank

CONTENTS

1.	INTRODUCTION	7
2.	OBJECTIVE	7
3.	DESCRIPTION	7
	APPENDIX – EDGEWOOD CHEMICAL BIOLOGICAL CENTER QIRL DATABASE	9

Blank

QUANTITATIVE INFRARED REFERENCE LIBRARY VOLUME I

1. INTRODUCTION

Recent technology developments in Fourier Transform Infrared (FTIR) spectroscopy, such as stand-off infrared detection of chemical agents and related compounds for monitoring applications, has created a need for condensed and vapor phase FTIR databases which utilize current technology. Old infrared databases are obsolete as they were collected on first generation instruments with poor signal-to-noise characteristics arising from a variety of instrumental variations (such as noisy A/D converters, wavelength calibration problems, etc.) relative to the capabilities of present day FTIR instrumentation. In addition, commercial infrared spectra compilations do not adequately address militarily significant, or directly related, compounds.

2. OBJECTIVE

The objective of this effort is to create, validate, and maintain a vapor phase FTIR database, with a focus on compounds of military significance or potential terrorist threat, using instrumentation that reflects current analytical capabilities.

DESCRIPTION

A series of quantitative concentrations of the analytes were established with a Kin-Tek model 491-M gas/vapor generation system. The Kin-Tek generator uses chemical-filled ¼" o.d. polytetraflouroethylene permeation tubes contained in a glass holder to establish continuous streams of chemical compounds. The glass permeation tube holder sits in a heated oven block, regulated by a digital temperature controller. Balance gas, regulated by digital mass flow controllers, is supplied to the vapor stream at two points: the permeation tube holder and downstream of the permeation tubes to provide additional diluent. The output concentration of the device can be varied by either changing the temperature of the oven block or the flow rate of the diluent gas. For the series of experiments in this paper, dry nitrogen, supplied by boiloff from a 230-L liquid nitrogen Dewar, was used.

The rate of mass flow from permeation tubes can be determined gravimetrically, by weighing the tubes before and after an operation. Because of the low volatilities of the compounds in these tests, this would have required potentially several weeks for each agent in order to accurately measure the mass loss. Furthermore, chemical agents tend to be chemically "sticky" and can adsorb to tubing walls and fittings. For this reason, the mass rate was determined with a secondary method. Using a mass flow controller, a measured volume of the effluent was drawn onto a sorbent tube filled with Tenax-TA for later desorption and analysis by gas chromatography. Analysis of the tubes was performed on an Agilent 5890A gas

chromatograph (GC) equipped with a Dynatherm thermal desorption apparatus and a flame ionization detector. The instrument was calibrated prior to each operation with external standards, prepared by serial dilution from the neat material in hexane, which were injected onto a sorbent tube and then desorbed into the GC. Six tubes were collected for each operation (agent). A statistical analysis of the data from the sorbent tubes showed typical RSD's of better than 5%.

Transfer lines between the generator and the FTIR gas cell were plumbed with ¼" o.d. Silicosteel® from Restek Corporation. This material minimizes adsorption by a wide variety of chemical compounds, enabling a more rapid stabilization of the concentration of the analyte in the gas cell.

Reference spectra of the effluent from the generator were acquired with a Protegé model Fourier transform infrared (FTIR) spectrometer from Thermo-Nicolet. The spectrometer is equipped with a mercury-cadmium-telluride (MCT) detector operating at cryogenic temperatures (achieved by filling the detector with liquid nitrogen prior to operation). The spectrometer is also outfitted with a 10-meter fixed pathlength gas cell from Thermo-Spectratech. Spectral conditions were 0.5 cm⁻¹ resolution, 3-term Blackman-Harris apodization, and co-adding of 64 scans to achieve the final spectra. Prior to any change in concentration, a fresh background (single beam) spectrum of the dry nitrogen was collected. As a quality check, a statistical analysis of the data was made, using peak heights to fit several representative bands at the vapor concentrations analyzed to a least squares fit, in order to determine compliance with Beer's Law.

APPENDIX

EDGEWOOD CHEMICAL BIOLOGICAL CENTER QIRL DATABASE

Edgewood Chemical Biological Center QIRL Database

QIRL Filename	Compound Name	CAS	Molecular Formula	CL (ppm-m)
QIRL0010	Acetone	67-64-1	C ₃ H ₆ O	100
QIRL0020	2-Propanol (isopropyl alcohol)	67-63-0	C ₃ H ₈ O	100
QIRL0030	Dimethyl methylphosphonate (DMMP)	9-62-952	$C_3H_9O_3P$	49
QIRL0040	Diethyl methylphosphonate (DEMP)	6-80-689	C ₅ H ₁₃ O ₃ P	38
QIRL0050	Triethyl phosphate (TEP)	78-40-0	C ₆ H ₁₅ O ₄ P	18
QIRL0060	Diisopropyl methylphosphonate (DIMP)	1445-75-6	C ₇ H ₁₇ O ₃ P	24
QIRL0070	Methyl salicylate	119-36-8	C ₈ H ₈ O ₃	171
QIRL0080	Triethyl phosphite	122-52-1	$C_6H_{15}O_3P$	84
QIRL0090	Diethyl phosphite	762-04-9	C₄H₁1O₃P	72
QIRL0100	Monoethanolamine (MEA)	141-43-5	C ₂ H ₇ NO	92
QIRL0110	Trimethyl phosphite	121-45-9	C₃H₃O₃P	93
QIRL0120	Dimethyl phosphite	868-85-9	C ₂ H ₇ O ₃ P	80
QIRL0130	Diethyl malonate (DEM)	105-53-3	C ₇ H ₁₂ O ₄	103
QIRL0140	Trimethyl phosphate (TMP)	512-56-1	C₃H₀O₄P	62
QIRL0150	1,4 Thioxane	15980-15-1	C₄H ₈ OS	147
QIRL0160	2-Chloroethyl ethyl sulfide (CEES)	693-07-2	C ₄ H ₉ CIS	86
QIRL0170	n-Butyl mercaptan (BUSH)	109-79-5	C4H10S	156
QIRL0180	2-(Diisopropylamino) ethanol	0-08-96	[(CH3)2CH]2NCH2CH2OH	97
QIRL0190	O,O-Diethyl methylphosphonothionate	6996-81-2	(CH3CH2O)2P(S)CH3	25
QIRL0200	O,S-Diethyl methylphosphonothionate	2511-10-6	(СН3СН2О)(СН3СН2S)2Р(О)СН3	74























































































































